



STANDARD DUTY
REAR-MOUNT

FINISH MOWERS

FEATURES

Deep 4.6-inch deck, baffling and unique rear discharge design ensures exceptional material distribution

Spring-loaded idler arms automatically maintain the correct tension on our custom-made belts

Tubular caster arms and heavy, tall deck rail supports (4.5-inches) for increased strength and durability

Turn acres of grass into well-groomed acres of lawn.

There's nothing more rewarding than a lawn that's finely groomed like a country club fairway. Especially when it doesn't take all day to make it look that way. That's why our finish mowers are engineered for speed, precision and enduring quality. The innovative rounded-front, tapered-side, rear-discharge deck allows you to reduce trim and mow with better maneuverability. And the heat-treated, alloy steel blades always give you a beautiful, high-precision cut on any type of grass.

YFM54 shown with optional chain shielding*

*All YFM Series finish mower models pass all applicable safety standards for thrown object and blade contact without chain shielding. However, if these units will be used in areas where the possibility of thrown objects could be hazardous to persons or property, it is strongly recommended that optional chain shielding be used for extra protection.

INNOVATIVE DESIGN AND TECHNOLOGY



ROUNDED FRONT CORNERS
and tapered deck sides improve maneuverability and grass discharge.



BOX-STYLE CONSTRUCTION
for superior deck strength.



Yanmar Finish Mowers Specifications

VEGETATION MANAGEMENT

| MODEL | STANDARD DUTY | | | MEDIUM DUTY | | |
|------------------------------|--|--------------------|--------|---|--------|--------|
| | YFM54 | YFM60 | YFM72 | YFM600 | YFM720 | YFM840 |
| Tractor PTO HP Range | 15-25 | 15-35 | 20-35 | 15-40 | 20-40 | 25-49 |
| Hitch/Quick Hitch Compatible | Limited Cat 1/No | | | Cat 1/Yes | | |
| Cutting Width (in.) | 54 | 60 | 72 | 69 | 72 | 84 |
| Weight (lbs) | 401 | 503 | 603 | 653 | 719 | 830 |
| Cutting Height Range (in.) | 1-4.5 | | | 1-5.5 | | 1-4.25 |
| Overall Width (in.) | 55 | 61 | 73 | 62 | 74 | 86 |
| Deck Material Thickness | 10-gauge | | | 8-gauge | | |
| Side Skirt (in.) | 10-gauge x 4.6 deep | 8-gauge x 4.6 deep | | 8 gauge x 5.375 w/ .5625 diam. skid rod bumper | | |
| Gearbox HP Rating | 25 | 35 | | 60 | | |
| Blade Tip Speed (FPM) | 16,200 | 18,030 | 18,000 | 18,100 | 18,000 | 17,900 |
| Blade Spindles/Bearings | 3 cast iron housings/greasable ball bearings | | | 3 cast iron housings/greasable tapered roller bearing | | |
| Tractor PTO Speed (RPM) | | | | 540 | | |
| Driveline Size | | | | Cat 3 | | |
| Belt | B-Section Kevlar® | | | B-Section Kevlar® with clutching cover | | |
| Belt Adjustment | | | | Spring-loaded idler | | |
| Rear Chain Shielding | | | | Optional | | |
| Mower Warranty | 1 year residential or 90 day commercial | | | 1 year | | |
| Gearbox Warranty (Limited) | 3 year homeowners or 1 year commercial | | | 6 years | | |