

MDB130

Mechanically Driven
Ditch Bank Mower



-  130" Horizontal Reach
-  Available in 540 or 1000 RPM
-  60" Cutting Width
-  Slip Clutch Protection
-  2" Cut Capacity



MDB130

SPECIFICATIONS

STANDARD EQUIPMENT & SPECIFICATIONS		
Cutting Width:		60"
Transport Width:		60"
Overall Width (Skid to Skid):		69 1/2"
Overall Length (Guard - Guard):		83 1/4"
Cutting Height:		1 1/2" - 12"
Hitch:		CAT 2 Std & CAT 3 Std
Blade Carrier:		Infinity - Cast
Blades:		1/2" x 4"
Blade Rotation:		Counter Clockwise
PTO HP Required (Min):		60 w/ 25% of Weight on Front Wheels
Min Tractor Weight:		8,000 lbs
Gearbox HP:	Center Deck	100 130
Tractor PTO Speed:		540 RPM 1000 RPM
Drive Type:		Mechanical
Mechanical Breakaway:		Std
Blade Tip Speed:	540 RPM 1000 RPM	13,904 14,128
Horizontal Reach (Max):		130"
Cutting Capacity (Max):		2"
Driveline Size:		CAT 4
Overload Protection:		Slip Clutch
Deck Thickness:		10 Ga
Side Skirt:		7 Ga x 9 1/8"
Range of Head Movement:		40° Up / 40° Down
Skid Shoes:		Std
Safety Guarding:		Single Chains
Weight (Approx):		1,900 lbs



Shown with Extra Equipment

