

TS10

SPECIFICATIONS

Cutting Width:	120"
Transport Width:	93"
Transport Height:	68"
Overall Length:	162"
Cutting Height:	1" - 15" (Dependent on Tire Size)
Height Adjustment:	3 1/2" x 8" Hydraulic Cylinder
Hitch:	Pull Type, Parallel Clevis
Blade Carrier:	Infinity - Steel
Blades:	1/2" x 3" High Lift
Tractor HP Required:	25 PTO
Cutting Capacity:	2"
Driveline ASABE:	CAT 4 CV (Main) / CAT 3 SC (Wing)
Deck Thickness:	12 Ga
Side Skirt:	1/4" x 10"
Tires & Wheels:	4 or 6, 20" Laminated, Aircraft or Foam Filled Rhino Trax
Wing Flex (Degrees):	90° Up, 22° Down
Safety Deflectors:	Deflectors or Chains
Tongue Weight:	720 lbs
Weight (Approx):	2,190 lbs

Show brush who's boss with the TS10 Flex-Wing Rotary Cutter.

Don't let the small size of the TS10 deceive you—it's packing some seriously heavy-duty guts. With a 120" cutting width and 1/2" x 3" blades, the TS10 is prepared to take on brush up to a full 2" in diameter.

The Flex-Wing deck design lets you cut on rolling terrain without having to make multiple passes—something fixed-deck cutters can only dream of doing. And with a transport width of only 93", the TS10 can get practically anywhere: through gates as narrow as 8', easily into storage, and into the bed of your pickup truck.

Turns out that bigger isn't always better.

TS10

10' FLEX-WING



SHOW BRUSH
WHO'S BOSS

RHINO

WALTERSCHEID EZ-LOC COLLAR

makes hookup easy (even for rookies)

REPLACEABLE SKID SHOES

for the simplest maintenance ever

AVERAGE MOWING TIME OF 4 MPH

so you can spend less time mowing and
more time living

SMOOTH, QUIET OPERATION

because no one wants a headache

HEAVY-DUTY TURN BUCKLES

for fewer breakdowns and less stress

