

TS12

12' Flex-Wing



Designed for tractors with 35 - 60 PTO HP



1 1/2" Cut Capacity



Low tongue weight for smaller HP tractors



Available with 4 or 6 tires



Unique "Wing-Bar" blade keeps it lightweight while protecting the gearbox output shaft



Large center section skid shoes and tapered wing shoes provide anti-scalping protection



Chain guards included for protection



Impressive short turn radius for tight spaces



TS12

SPECIFICATIONS

Specifications	TS12
Cutting Width:	144"
Transport Width:	97"
Overall Width:	155"
Overall Length:	148"
Cutting Height: *	2" - 12"
Jack Stand:	Std
Blade Carrier:	Wing Pan
Blades:	1/2" x 3"
Blade Overlap:	6"
HP Required:	35 - 60 PTO
Gearbox Rating: **	
Divider	160 HP
Center & Wing	65 HP
Output Shaft Diameter:	1 9/16"
Blade Tip Speed:	
Center 540 RPM	14,504 FPM
Wing 540 RPM	13,925 FPM
Cut Capacity:	1 1/2" Diameter
Driveline Size:	CAT 4 Equal Angle/ CAT 3
Deck Thickness:	12 Ga
Driveline Protection:	Slip Clutch
Center:	10 Ga Bottom, 12 Ga Top
Wings:	Double 12 Ga
Side Skirt:	1/4" x 11 1/2"
Tires & Wheels:	Foam Filled Aircraft or Laminated Tires
(4 or 6) OR	
Wing Flex (Degrees):	88° Up / 25° Dn
Safety Tow Chain:	Std
LED Light Kit:	Std
Safety Deflectors:	Chain Guards
Wheel Base:	126 1/4"
Tongue Weight:	748 lbs
Weight (Approx):	2,750 lbs

* Cutting height dependent on tire size.

** Gearbox rating based on field performance.



TS12 WING-BAR
BLADE CARRIER