

FLEX-WINGS

6140 | 6200



Divider gearbox rated for 250 HP, with outboard boxes rated at 225 HP, each with a 6 year limited warranty!



Smooth top center deck is one of the strongest and easiest to clean of any cutter in the industry!



4 1/2" diameter cut capacity and fast blade tip speeds for a clean cut in heavy mowing applications!



Available with 540 or 1000 RPM drivelines.



Obstruction-free underside of deck for enhanced airflow in the cutting chamber to distribute cut material evenly.



CAT 6 CV main driveline and CAT 6 HD wing drivelines are standard, with 2 year limited driveline warranty!



6140 available with right wing and counterweight.



Three blade carrier choices for the 6200 and two blade carrier choices for the 6140 are available to match your application needs.

6140 | 6200 SPECIFICATIONS

Specifications	6140	6200
Cutting Width	162"	240"
Transport Width	106"	115"
Transport Height	100"	100"
Overall Width	170"	248"
Overall Length	216"	216"
Cutting Height*	2" - 16"	2" - 16"
Height Adjustment	Hydraulic Cylinder	Hydraulic Cylinder
Jack Stand	Standard	Standard
Blade Carrier	Dog Bone or Oval Pan	Dog Bone, Oval Pan, or Shredder Bar
Blades	1/2" x 4" Updraft	1/2" x 4" Updraft
HP Required (Min)	80 PTO HP	80 PTO HP
Gearbox Rating**	250 HP Divider 225 HP Center & Wing	250 HP Divider 225 HP Center & Wing
Output Shaft Diameter	3"	3"
Blade Tip Speed (FPM)	540 RPM: 15,675 Center/15,703 Wing 1000 RPM: 16,054 Center/15,804 Wing	540 RPM: 15,675 Center/15,703 Wing 1000 RPM: 16,054 Center/15,804 Wing
Cutting Capacity	4 1/2"	4 1/2"
Driveline Size	CAT 6 CV Main/CAT 6 HD Wing	CAT 6 CV Main/CAT 6 HD Wing
Deck Thickness	10 Ga Top/Bottom	10 Ga Top/Bottom
Side Skirt	1/4" x 12"	1/4" x 12"
Tire & Wheel Options	Laminated, Pneumatic, Foam Filled	Laminated, Pneumatic, Foam Filled
Wing Lift Hydraulics	Standard	Standard
Wing Flex (Degrees)	90° Up/ 22° Down	90° Up/ 22° Down
Safety Tow Chain	Standard	Standard
Deck Rings	Standard	Standard
Safety Deflector	Single or Double Chain Guards	Single or Double Chain Guards
LED Light Kit	Standard	Standard
Weight (Approx)***	7,281 lbs	7,490 lbs

* Cutting Height dependent on tire size

** Gearbox Rating based on field performance

*** Weight Varies with machine configuration



1020 S. Sangamon Ave | Gibson City, IL 60936
TEL: 800-221-2855 (Opt 3) | Fax: 877-408-3298

WWW.RHINOAG.COM



6200-0316-DYNA